



MODEL	A	B	C	D	E	F	G	H	J	K	L	FILTER SIZE
4000	58 1/4	54	27 1/8	61 1/2	48	5 1/8	18	50 3/16	22 1/2	5 3/8	3 5/8	(2) 16x25x2 (1) 20x25x2
5000	71 1/4	54	27 1/8	74 1/2	54	8 5/8	20	62 3/16	22 1/2	3	2 3/16	(4) 16 x 25 x 2
6000	85 1/4	60	27 1/8	88 1/2	60	12 5/8	20	75 1/4	22 1/2	7 3/8	3 5/8	(3) 25 x 25 x 2
8000	85 1/4	67	27 1/8	88 1/2	72	6 5/8	24	76 3/4	22 1/2	5	2 3/16	(8) 16 x 20 x 2
10000	105 1/4	67	27 1/8	108 1/2	90	7 5/8	24	92 3/4	30 1/2	11 1/2	2 3/16	(8) 16 x 20 x 2, (2) 16 x 25 x 2
12000	116 1/4	83	34 1/8	120 1/2	90	13 1/8	28	104 1/2	30 1/2	8 3/16	2 3/16	(8) 16 x 20 x 2, (2) 16 x 25 x 2

D101305

**If the unit has Electric Heat, the Duct Heater is shipped loose and field mounted.**

- Right-hand unit shown, left-hand unit opposite.
- Coil connections determined by facing the return-air opening.
- Electrical junction box is located on the same side as the coil connections.
- Unit must be installed level and condensate drain lines should be trapped.
- Drain pan is powder-coated epoxy with a 1/4" thick closed-cell insulation and has 3/4" to 1" NPT primary and (Optional) secondary drain connections.
- Entire cabinet, scroll and blower wheel are heavy-gauge, galvanized steel.
- Coil connections: range from 1/2" to 2 1/2". See Specification Guide.